

# SURVEY OF PAKISTAN INVITATION TO BID

<u>Survey of Pakistan</u> a <u>National Surveying & Mapping Department</u> invites sealed bids from the <u>Original manufacturers/authorized distributers/suppliers/contractors</u> <u>etc.</u>, registered with Income Tax & Sales Tax Departments for supply of following:

Sr. #	Description of Equipment/Furniture	Qty	<b>Closing Date</b>
1	Total Station	3	
2	High Precision Digital Level 0.3 mm accuracy with all accessories including stave	2	
3	Level Staves for WILD N-3 HP Level or equivalent	2	
4	Wooden Tripod for Existing WILD N-3 HP Level or equivalent	4	
5	Computer Table	47	
6	Computer Chair	80	10-02-2021
7	Office Chair	30	
8	UPS 2KVA	5	
9	Plotter 44" Size	2	
10	Scanner-Size (A0) 48"	2	
11	Photocopier	2	
12	LED TV 110"	2	
13	Printer A4 Size	9	

2). Bidding documents, containing detailed terms and conditions, method of procurement, procedure for submission of bids, bid security, bid validity, opening of bid, evaluation criteria, clarification/rejection of bids, performance guarantee etc., are available for the interested bidders at <u>website of Public Procurement Regulatory Authority</u>, <u>(www.ppra.org.pk.)</u>, which can be downloaded.

3). The bids, prepared in accordance with the instructions in the bidding documents, must reach at <u>Survey of Pakistan</u>, <u>Murree Road</u>, <u>Faizabad</u>, <u>Rawalpindi duly addressed to the Chairman Purchase Committee</u> on or before <u>10-02-2021 at 11:00 hrs</u>. Bids will be opened the same day at <u>11:30 hrs</u>. This advertisement is also available on Department's website at <u>www.surveyofpakistan.gov.pk</u>.

(NOOR ELAHI) Deputy Surveyor General Chairman Purchase Committee

## **TERMS & CONDITIONS**

- 1. Applications on prescribed form (attached) along with technical specifications (compliance sheet) and contract, which can be downloaded from the website of PPRA, should reach the Chairman Purchase Committee, Survey of Pakistan, Faizabad, Rawalpindi by registered post/courier latest by 11:00 hours on 10-02-2021. These will be opened at 11:30 hours on the same day in the presence of bidders their authorized representatives.
- 2. The envelope shall be marked as "FINANCIAL PROPOSAL" & "TECHNICAL PROPOSAL" in bold and legible letters to avoid confusion. Initially, only envelopes marked as Technical Proposal shall be opened and envelopes marked as Financial Proposal shall be retained in the custody of Chairman Purchase Committee. After the evaluation & recommendations by the Technical Evaluation Committee concerned, Financial Proposals of only technically accepted bids will be opened. The Financial Proposals of bids found technically non-responsive shall be returned un-opened to the respective bidders.
- 3. 3% earnest money in shape of pay order/bank draft in the name of Chairman Purchase Committee, Survey of Pakistan, Rawalpindi should be enclosed in the envelope containing Financial Bid. However, the certificate for attachment be indicated in technical bid, otherwise, the same will be rejected at the opening stage.
- 4. Successful bidder(s) will be required to execute agreement governing the terms & conditions of the contract.
- 5. All the bidders are requested to offer the latest model. Accepted/approved model shall not be replaced at any stage even with superior model. Supplier's earnest money will be forfeited and supply order will be cancelled.
- 6. Procuring agency may reject any or all bids subject to the relevant provisions of PPRA Rules.
- 7. Only registers suppliers who are on Active Tax Payers List (ATL) of FBR are eligible to supply goods to the Government departments.
- 8. The supplier should attach a proof that he is on ATL of FBR Data Base. In other case his payment would be stopped till he files his mandatory return and appears on ATL of FBR.
- 9. The prices should be inclusive of all leviable taxes.
- 10. Bids will be valid for 120 x days from the date of opening of bid.
- 11. The bidders shall have to give demo of their offered model during Technical Evaluation for analysis.
- 12. The bidders should also provide the detail price analysis of the items/accessories in their Financial Proposal alognwith unit rate with GST.
- 13. The method of procurement is single stage two envelopes as per PPRA's Rule-36(b).
- 14. The successful bidder shall be liable to give full/justifiable training of their approved model.
- 15. Quantity of items can be increased or decreased subject to availability of funds.
- 16. Compliance sheet (attached) must be furnished duly filled in, otherwise tender will not be entertained.
- 17. Copy of CNIC must be attached with the Technical & Financial bids.
- 18. For more information, please contact with Mr. Muhammad Asghar, Senior Stores Officer at telephone No. 051-9290227.

# **EVALUATION CRITERIA**

Technical Evaluation Report of the Technical Proposals will be made as per tender specifications and considering their eligibility and qualification without the reference to the price as per PPRA Rule 36 (b)(v).

2. Only the Financial Proposals of those bidders whose Technical Proposals have technically been recommended by Technical Evaluation Committee of the department will be opened publicly as per PPRA Rule 36 (b)(viii).

3. The bid fulfilling the above mentioned criteria and PPRA Rule 36(b)(ix) will be declared the most advantageous bid.

**Note:** Evaluation of Digital Level & Total Station will be made as per given Proforma A-1 & B-1 and A-2 & B-2.

#### PRESCRIBED APPLICATION FORM FOR TENDERING OF PROCUREMENT OF EQUIPMENT

(To be printed on firm/supplier's letter head duly signed by the authorized representative)

The Chairman Purchase Committee, Survey of Pakistan, Faizabad, Rawalpindi.

We have gone through all the terms and conditions contained in above mentioned documents and those, which are the part of tender.

We fully agree to abide by the terms and conditions contained in the said documents and therefore hereby submit Technical as well as Financial Proposals for the following:

#### AUTHORISED SIGNATURE NAME & SEAL OF FIRM/SUPPLIER

### **SPECIFICATION OF TOTAL STATION**

#### **TENDER SPECIFICATIONS**

#### TELESCOPE

a. Image	Erect	
b. Magnification	30X	
c. Field of View	1° 30'-1° 25'	
d. Focusing Range	2.0 m to infinity	
e. Resolving Power	≤ 3''	
a. Tilt compensation method	dual axis	
b. Tilt compensation range	≥3''	
c. Angle accuracy	≤5"	
d. Displayed resolution	less than 1"	
a. Range with reflector	≥5000m with 1 pris	m
B. Range without reflector	600-800m	
c. EDM accuracy	≤ (2mm+ 2ppm) of	
d. Measuring time	Fine: ≤ 1.0s (initial	
	Rapid: ≤ 0.6s (Initia	•
	Tracking: ≤ 0.4s (Ini	tial 1.3s)
OPTICAL PLUMMET		
a. Magnification	≥2.2x	
b. Focusing Range	0.5m to infinity	
c. Level		e Vial 30 seconds per division/ (2 mm)
d taxaa		10 minutes per division/ (2 mm)
d. Laser	Red laser Diode, Bea	am Accuracy <= 1.0mm @ 1.3m
KEYBOARD AND DISPLAY		
a. Control Panel Location		On Dual face
b. Display		Dual Coloured Touch Screen display
c. Graphics d. Interface		320x240 pixels (Q VGA)
		windows
e. Key and display illumination		
f. 5 Brightness level		
APPLICATION PROGRAM		
a. Topographic Observations		
b. Route Surveying		
<ul><li>c. Resection</li><li>d. Offset Measurement</li></ul>		
e. Missing Line/RDM f. Surface Area Calculation		
<b>- - - - - - - - - -</b>		
0	nt	
j. Stake Out		

k. Intersection

#### SPECIAL REQUIREMENTS

Certificate of origin

Certificate from chamber of commerce	Certificate from Chamber of Commerce with serial Number of Total Stations shipped against this order from place of shipment
ACCESSORIES	
a. Original/ Branded Accessories with strong	g carrying case
b. Data transfer cable	01
c. Data transfer/Processing Software with co	omplete features license
d. Rechargeable Batteries	02
e. Battery charger	01
f. CD containing instruction manual	01
g. Prism with target plate	03
h. Prism Pole	2.5 meter 3 with each Total Station
i. Display	02
j. Detachable tribrach	02
k. lens cover set	01
I. cleaning brush	01
m. cover of durable plastic	
n. Shock absorbing carrying case with should	der strap etc in complete
o. Heavy duty wooden tripod/Fibre glass	01
p. Bipod/Catcher for prism pole Aluminium	02
q. Canvas Covers / <b>Bags</b>	For Total Station Box, Tripod, Prism, Prism
pole, Bipod	
DATA STORAGE	
a. Capacity	≥50,000 points on board
b. Data formats	GSI/DXF/LANDXML/CSV/user definable
ASCII formats	
c. Interface	USB, Serial
FOCUSING MODE	
Manual focus mode	
PHYSICAL	
a. Weight	≤10 kg
b. Temperature range	-20 to +60 C fully operational
c. Humidity	0 to ≥90% RH
d. Protection splash waterproof dustproof	
e. IP rating should be minimum 65	
POWER	
a. Batteries LI-ion rechargeable	Dual battery slots for protecting memory
	during changing of batteries
b. Capacity	Continuous angle-only measurement: 12 h
	Distance/angle measurement/ AF every 30 s
c. Recharge time	6 hours
TRAINING	

Training for operation and preventive maintenance of equipment (Hardware and software) for 02 weeks free of charge.

#### WARRANTY

One year after commission on site, defective parts/assemblies will be replaced by the bidder free of charge within warranty period. After sales & services guaranty of 02 years. **Terms & Conditions** 

- 1. Bid from the original manufacturer (OEM) or his Authorize Agent of the Total Station will be considered for technical evaluation.
- 2. OEM (Original Equipment Manufacturer) must have reasonable experience of manufacturing Total Station instrument. Any sale contract / document to be provided as proof. Preference will be given on basis of more experience.
- 3. Workshop and after sale service in Pakistan must be present to ensure in time availability of spares and after sale technical support to Survey of Pakistan. E-mail, telephone, fax No. and address of workshop to be provided with technical bid for confirmation during technical evaluation. Evaluation team may inspect workshop.
- 4. The bidder must provide OEM certificate of main equipment, technical specifications, broachers and drawings of each item in schedule of requirement of quoted model in English.
- 5. All bidders are advised to comply strictly with the tender specifications and no deviation shall be allowed.
- 6. The system must be based on latest design (Hardware & Software), model and technology.
- 7. Before opening of financial tender, responsive bidder will be responsible for on ground practical demonstration of the quoted instruments along with all accessories in Survey of Pakistan headquarters Rawalpindi, Pakistan. The performance and quality will be technically evaluated by technical committee of SOP as per tender specifications.
- 8. Evaluation criteria for Technical Evaluation of Total Station Level is based on
  - 100% compliance of each sub-item of Tender Specifications as mentioned in Proforma-A-2 will be required.
  - If the firm qualifies 100% compliance on the basis of Proforma A-2, the firm has to demonstrate the performance to evaluate the user interface, quality, OEM/ authorized Agent Experience of the firm. Availability of after sale services /workshop and performance of the equipment.
  - On the basis of Proforma B-2 the bidder obtaining 70 or more marks will be technically qualified.

#### Evaluation criteria is given in attached

- I. Proforma A-2.
- II. Proforma B-2.

#### Note:

# SPECIFICATION OF TOTAL STATION (Compliance Sheet)

#### TENDER SPECIFICATIONS

Sr. # Functions/	Specifications	Compliance/
Peripherals	•	Bidder Response
TELESCOPE		
a. Image	Erect	
b. Magnification	30X	
c. Field of View	1° 30'-1° 25'	
d. Focusing Range	2.0 m to infinity	
e. Resolving Power	≤ 3''	
ANGLE MEASUREMENT	-	
a. Tilt compensation me	ethod dual axis	
b. Tilt compensation ra	nge ≥3"	
c. Angle accuracy	≤5"	
d. Displayed resolution	less than 1"	
DISTANCE MEASUREM		
a. Range with reflector	≥5000m with 1 prism	
B. Range without reflec		
c. EDM accuracy	≤ (2mm+ 2ppm) of distance	
d. Measuring time	Fine: $\leq$ 1.0s (initial 1.5s)	
	Rapid: $\leq 0.6s$ (Initial 1.3s)	
	Tracking: ≤ 0.4s (Initial 1.3s)	
OPTICAL PLUMMET		
a. Magnification	≥2.2x	
b. Focusing Range	0.5m to infinity	
c. Level	Plate/tubular Bubble Vial 30 seconds	
per division/ (2 mm)		
	Circular Bubble Vial 10 minutes per	
	division/ (2 mm)	
d. Laser	Red laser Diode, Beam Accuracy <=	
1.0mm @ 1.3m	A.V.	
KEYBOARD AND DISPL		
a. Control Panel Locatio	n On Dual face Dual Coloured	
b. Display Touch Scroon display	Dual Coloured	
Touch Screen display c. Graphics	320x240 pixels (Q	
VGA)	SZUXZ4U PIXEIS (Q	
d. Interface	windows	
e. Key and display illum		
f. 5 Brightness level	indion	
1. 5 BIGHTIC35 IEVEL		
APPLICATION PROGRA	Μ	
I. Topographic Observ	vations	
m. Route Surveying		
n. Resection		

o. Offset Measurement		
p. Missing Line/RDM		
q. Surface Area Calculation		
r. Point to Line		
s. 3D Coordinate measurement		
t. Remote Elevation Measurement		
u. Stake Out		
v. Intersection		
SPECIAL REQUIREMENTS		
Certificate of origin	From manufacturer with	
every equipment in box		
Certificate from chamber of commerce	Certificate from Chamber	
of Commerce with serial		
	Number of Total Stations	
shipped against this order		
from place of shipment		
ACCESSORIES		
a. Original/ Branded Accessories with stror	ng carrying case	
b. Data transfer cable	01	
c. Data transfer/Processing Software with	complete features license	
d. Rechargeable Batteries	02	
e. Battery charger	01	
f. CD containing instruction manual	01	
g. Prism with target plate	03	
h. Prism Pole	2.5 meter 3 with	
each Total Station		
i. Display	02	
j. Detachable tribrach	02	
k. lens cover set	01	
I. cleaning brush	01	
m. cover of durable plastic		
n. Shock absorbing carrying case with shou	Ilder strap etc in complete	
o. Heavy duty wooden tripod/Fibre glass	01	
p. Bipod/Catcher for prism pole Aluminium		
q. Canvas Covers / <b>Bags</b>	For Total Station	
Box, Tripod, Prism, Prism pole, Bipod		
DATA STORAGE		
a. Capacity	≥50,000 points on	
board		
b. Data formats		
GSI/DXF/LANDXML/CSV/user defin	ahle ASCII formats	
c. Interface	USB, Serial	
FOCUSING MODE	030, Serial	
Manual focus mode		
PHYSICAL		
	<10 kg	
a. Weight	≤10 kg	
b. Temperature range	-20 to +60 C fully	
operational		

c. Humidity	0 to ≥90% RH	
d. Protection splash waterproof dustproof	• •• =• •• •• •	
e. IP rating should be minimum 65		
POWER		
a. Batteries LI-ion rechargeable	Dual battery slots	
	for protecting	
	memory during	
	changing of	
	batteries	
b. Capacity	Continuous angle-	
only measurement: 12 h		
	Distance/angle	
measurement/ AF every 30 s	Distance, angle	
c. Recharge time	6 hours	
TRAINING	o nours	
Training for operation and preventive main	tenance of equipment	
(Hardware and software)	contraction of equipment	
for 02 weeks free of charge.		
for oz weeks nee of charge.		
WARRANTY		
One year after commission on site, defective pa	arts/assemblies will be	
replaced by the bidder	arts/assemblies will be	
free of charge within warranty period. After sa	les & services guaranty	
of 02 years.	ies & services guaranty	
Terms & Conditions		
9. Bid from the original manufacturer (OEN	A) or his Authorizo	
<b>-</b>	•	
Agent of the Total Station will be considered fo		
10. OEM (Original Equipment Manuf	-	
reasonable experience of manufacturing Total s		
sale contract / document to be provided as pr	oor. Preference will be	
given on basis of more experience.		
11. Workshop and after sale service in Pakis	•	
ensure in time availability of spares and after sa		
Survey of Pakistan. E-mail, telephone, fax		
workshop to be provided with technical bid f	-	
technical evaluation. Evaluation team may insp	•	
12. The bidder must provide OEM certifica	• •	
technical specifications, broachers and draw	•	
schedule of requirement of quoted model in En	-	
13. All bidders are advised to comply strictly		
specifications and no deviation shall be allowed		
14. The system must be based on latest des	lign (Hardware &	
Software), model and technology.		
15. Before opening of financial tender, res	-	
responsible for on ground practical demons	•	
instruments along with all accessories in	-	
headquarters Rawalpindi, Pakistan. The perfor		
be technically evaluated by technical committee	ee of SOP as per tender	
specifications.	'	

16.	Evaluation criteria for Technical Evaluation of Total Station					
Level i	Level is based on					
•	<ul> <li>100% compliance of each sub-item of Tender Specifications as mentioned in Proforma-A-2 will be required.</li> <li>If the firm qualifies 100% compliance on the basis of Proforma A-2, the firm has to demonstrate the performance to evaluate the user interface, quality, OEM/ authorized Agent Experience of the firm. Availability of after sale services /workshop and performance of the equipment.</li> <li>On the basis of Proforma B-2 the bidder obtaining 70 or more</li> </ul>					
	marks will be technically qualified.					
Note:						
	Evaluation criteria is given in attached					
١.	Proforma A-2.					
П.	Proforma B-2.					

# SPECIFICATION OF HIGH PRECISION DIGITAL LEVEL 0.3 MM ACCURACY WITH ALL ACCESSORIES INCLUDING STAVE

#### LIST OF ITEMS

1.	H.P Level			02
2.	Processing Software (Full packa	ige)		01
3.	3. Imported heavy duty branded wooden/Fibre glass Tripods			02
4.	I. Invar Bar coded Staves with wooden box			05
5.	Spare Batteries			02
6.	Stave holder			04
7.	Foot plates			04
8.	H.P Level cover			02
9.	All other standard accessories	with arti	cle number of same brand	d (i.e batteries, chargers,
	measuring taps and carrying ca	ses etc)		
HE	IGHT MEASUREMENT:	-		
Le	vel Accuracy	0.3 m	m	
DI	STANCE MEASUREMENT:			
Dis	stance Accuracy (≥100m range)	±0.2%	of the distance	
M	EASUREMENT RANGE:			
Me	easurement range	≤1.8 r	neter to ≥100 meter	
Me	easurement time	≤ 2.5 :	sec	
FO	CUS:			
Fo	cus Type	Auto		
Au	to focus Range	≤1.8 r	n to ≥100 meter	
Au	to Focus time	≤4 Se	c (less is better)	
<u>SP</u>	ECIAL REQUIREMENTS			
Ce	rtificate of origin:		From manufacturer wit	h every equipment in box
Ce	rtificate from chamber of comm	nerce:	Certificate from Chamb	er of Commerce with serial
			Number of Digital High	Precise Level shipped
			against this order from	place of shipment
<u>CC</u>	MPENSATOR:			
W	orking range	± 9'		
Со	mpensator Accuracy	0.3''		
Ma	agnetic field sensitivity	Magn	etic Damping system	
<u>IN</u>	<u>TERFACES</u>			
RS	232/USB/Mini USB			
DA	ATA STORAGE			
Int	ernal 10,000 (or greater) measu	rements	and USB Storage	
GE	NERAL			
Dis	splay	Colou	r touch screen with LED b	acklight (Sunlight
		reada	bility).	
Te	lescope Magnification	32x		
Mi	nimum focus distance	≤1.5 r	n	
Ele	ectronic level bubble	must	be available	
Int	ernal battery / operating time		ngeable Lithium-Ion / 10	- 12 h
W	orking temperature range	-20 °C	C to +50 °C	

Dust / Water (IEC 60529) Humidity

#### TRAINING

Training for operation and preventive maintenance of equipment (Hardware and software) for 02 weeks free of charge.

#### WARRANTY

One year after commission on site, defective parts/assemblies will be replaced by the bidder free of charge within warranty period. After sales & services guaranty of 02 years.

#### **Terms & Conditions**

17. Bid from the original manufacturer (OEM) or his Authorize Agent of the Digital High Precise Level will be considered for technical evaluation.

18. OEM (Original Equipment Manufacturer) must have reasonable experience of manufacturing Digital High Precise Level instrument. Any sale contract / document to be provided as proof. Preference will be given on basis of more experience.

19. Workshop and after sale service in Pakistan must be present to ensure in time availability of spares and after sale technical support to Survey of Pakistan. E-mail, telephone, fax No. and address of workshop to be provided with technical bid for confirmation during technical evaluation. Evaluation team may inspect workshop.

20. The bidder must provide OEM certificate of main equipment, technical specifications, broachers and drawings of each item in schedule of requirement of quoted model in English.

21. All bidders are advised to comply strictly with the tender specifications and no deviation shall be allowed.

22. The system must be based on latest design (Hardware & Software), model and technology.

23. Before opening of financial tender, responsive bidder will be responsible for on ground practical demonstration of the quoted instruments along with all accessories in Survey of Pakistan headquarters Rawalpindi, Pakistan. The performance and quality will be technically evaluated by technical committee of SOP as per tender specifications.

24. Evaluation criteria for Technical Evaluation of Digital High Precise Level is based on

- 100% compliance of each sub-item of Tender Specifications as mentioned in Proforma-A-1 will be required.
- If the firm qualifies 100% compliance on the basis of Proforma A-1, the firm has to demonstrate the performance to evaluate the user interface, quality, OEM/ authorized Agent Experience of the firm. Availability of after sale services /workshop and performance of the equipment.
- On the basis of Proforma B-1 the bidder obtaining 70 or more marks will be technically qualified.

Note:

#### Evaluation criteria is given in attached

- I. Proforma A-1.
- II. Proforma B-1.

#### Note:

# SPECIFICATION OF HIGH PRECISION DIGITAL LEVEL 0.3 MM ACCURACY WITH ALL ACCESSORIES INCLUDING STAVE

(Compliance Sheet)

Nr II	unctions/	Specificat	tions			Compliance/
LIST OF IT	eripherals	-				Bidder Response
	EIVIS					-
1. H.P Lev	el				02	
	sing Software (		•		01	
			-	ibre glass Tripods	02	
4. Invar Ba	ar coded Stave	s with wood	len box	05		
5. Spare B					02	
6. Stave h					04	
7. Foot pla				04		
8. H.P Lev					02	
				e number of same bra	nd	
(i.e batter	ries, chargers,	measuring ta	aps and	carrying cases etc)		
HEIGHT N	1EASUREMEN	<u>r:</u>				
Level Accu	uracy		0.3 mr	n		
DISTANCE	E MEASUREME	NT:				
Distance A	Accuracy (≥100	)m range)	±0.2%	of the distance		
MEASURE	EMENT RANGE	•				
Measuren	nent range		≤1.8 m	neter to ≥100 meter		
Measuren	nent time		≤ 2.5 s	ec		
FOCUS:						
Focus Typ	e		Auto			
Auto focu	s Range		≤1.8 m	n to ≥100 meter		
Auto Focu	ıs time		≤4 Sec	: (less is better)		
SPECIAL R	REQUIREMENT	<u>s</u>				
Certificate	e of origin:			From manufacturer w	vith	
every equ	ipment in box					
Certificate	e from chamb	er of comme	erce:	Certificate from Char	nber	
				of Commerce with se	erial	
				Number of Digital Hi	gh	
				Precise Level shipped	ł	
				against this order fro	m	
				place of shipment		
COMPENS	SATOR:					
Working r	ange		± 9'			
Compensa	ator Accuracy		0.3''			
Magnetic	field sensitivit	У	Magne	etic Damping system		
<b>INTERFAC</b>	<u>ES</u>					
RS232/US	B/Mini USB					
DATA STC						
Internal 1	0,000 (or grea	ter) measure	ements	and USB Storage		
<u>GENERAL</u>						

Display	Colour touch screen with LED				
	backlight (Sunlight readability).				
Telescope Magnification	32x				
Minimum focus distance	≤1.5 m				
Electronic level bubble	must be available				
Internal battery / operating time	Exchangeable Lithium-Ion / 10 -				
12 h					
Working temperature range	-20 °C to +50 °C				
Dust / Water (IEC 60529)	IP 54 or better				
Humidity	95%, non-condensing				
TRAINING					
Training for operation and prevent	ve maintenance of equipment				
(Hardware and software)					
for 02 weeks free of charge.					
WARRANTY					
	, defective parts/assemblies will be				
replaced by the bidder	,,,,				
	iod. After sales & services guaranty				
of 02 years.					
Terms & Conditions					
	nufacturer (OEM) or his Authorize				
_	evel will be considered for technical				
evaluation.					
IV. OEM (Original Equipment Manufacturer) must have					
reasonable experience of manufacturing Digital High Precise Level					
instrument. Any sale contract / document to be provided as proof.					
Preference will be given on basis of					
-	rvice in Pakistan must be present to				
ensure in time availability of spares and after sale technical support to					
Survey of Pakistan. E-mail, telephone, fax No. and address of					
workshop to be provided with technical bid for confirmation during					
technical evaluation. Evaluation team may inspect workshop.					
	EM certificate of main equipment,				
	s and drawings of each item in				
schedule of requirement of quoted	-				
VII. All bidders are advised to					
specifications and no deviation shall be allowed.					
VIII. The system must be based on latest design (Hardware &					
Software), model and technology.					
IX. Before opening of financia					
responsible for on ground practi					
instruments along with all ac					
headquarters Rawalpindi, Pakistan					
be technically evaluated by technical committee of SOP as per tender					
specifications.	·				
X. Evaluation criteria for Technical Evaluation of Digital High					
Precise Level is based on					
<ul> <li>100% compliance of each sub-item of Tender Specifications as</li> </ul>					
mentioned in Proforma-A-1	-				

•	If the firm qualifies 100% compliance on the basis of Proforma A-1, the firm has to demonstrate the performance to evaluate the user interface, quality, OEM/ authorized Agent Experience of the firm. Availability of after sale services /workshop and performance of the equipment. On the basis of Proforma B-1 the bidder obtaining 70 or more	
Note:	marks will be technically qualified.	
Note:	Evaluation criteria is given in attached	
١.	Proforma A-1.	
١١.	Proforma B-1.	

# SPECIFICATIONS OF LEVEL STAVE FOR WILD N-3 HP LEVEL OR EQUIVALENT

 Staves for Wild N-3 High Precise Level (Aluminum/wooden) length 3m= 05 pairs

# SPECIFICATIONS OF LEVEL STAVE FOR WILD N-3 HP LEVEL OR EQUIVALENT (Compliance Sheet)

Sr. #	Functions/ Peripherals	Specifications	Compliance/ Bidder Response
<ul> <li>Staves for Wild N-3 High Precise Level</li> </ul>			
	(Aluminum/wooden) length 3m= <b>05 pairs</b>		

#### Note:

# SPECIFICATIONS OF WOODEN TRIPOD FOR EXISTING WILD N-3 HP LEVEL OR EQUIVALENT

 Heavy Duty Wooden Tripod for Existing Wild N-3 High Precise Level = 10 nos.

## SPECIFICATIONS FOR WOODEN TRIPOD FOR EXISTING WILD N-3 HP LEVEL OR EQUIVALENT (Compliance Sheet)

Sr. #	Functions/ Peripherals	Specifications	Compliance/ Bidder Response
<ul> <li>Heavy Duty Wooden Tripod for Existing Wild N-3</li> </ul>			
	High Precise Level = <b>10 nos.</b>		

#### Note:

### **SPECIFICATIONS OF COMPUTER TABLE**

Size:	1375 mm x 600 mm table top size, 1300 mm x 525 mm table frame size with 750 mm height. Frame legs fitted with plastic boots.
Description:	Square iron pipe structure measuring 25 mm x 25 mm with 14 - 16 SWG thickness and painted in high quality silver colour enamel. 1 x horizontal bracing frame at the level of 400 mm above ground along the two shorter sides and along long side at back. 1 x horizontal bracing frame along around 75 mm above the ground.
Table Top:	¾" thick high quality sheesham vim board with high quality polish in walnut colour and fixed with high quality plastic edging (gola)
Drawer:	1 x 300 mm wide x 450 mm long with 100 mm depth drawer made up of ¾" thick high quality sheesham vim board with plastic gola all around and fitted with high-quality lock. Applied with high quality polish in walnut colour
Keyboard & Mouse tray:	1 x 600 mm wide x 250 mm long with 55 mm depth keyboard & mouse tray made up of ¾" thick high quality sheesham vim board with plastic gola all around. Applied with high quality polish in walnut colour
Iron/steel channels:	Steel color high strength soft-close iron/steel channels having 400 mm length for drawer and 250 mm length for keyboard/mouse tray.

#### Note:

### SPECIFICATIONS OF COMPUTER TABLE (Compliance Sheet)

Sr. #	Functions/ Peripherals	Specifications	Compliance/ Bidder Response
Size:		1375 mm x 600 mm table top size, 1300 mm x 525 mm table frame size with 750 mm height. Frame legs fitted with plastic boots.	
Description:		Square iron pipe structure measuring 25 mm x 25 mm with 14 - 16 SWG thickness and painted in high quality silver colour enamel. 1 x horizontal bracing frame at the level of 400 mm above ground along the two shorter sides and along long side at back. 1 x horizontal bracing frame along around 75 mm above the ground.	
Table T	ōp:)	¾" thick high quality sheesham vim board with high quality polish in walnut colour and fixed with high quality plastic edging (gola	
Drawer:		1 x 300 mm wide x 450 mm long with 100 mm depth drawer made up of ¾" thick high quality sheesham vim board with plastic gola all around and fitted with high-quality lock. Applied with high quality polish in walnut colour	
Keyboard & Mouse		1 x 600 mm wide x 250 mm long with 55 mm depth keyboard & mouse tray made up of ¾" thick high quality sheesham vim board with plastic gola all around. Applied with high quality polish in walnut colour	
Iron/steel channels:		Steel color high strength soft-close iron/steel channels having 400 mm length for drawer and 250 mm length for keyboard/mouse tray.	

#### Note:

### **SPECIFICATIONS OF COMPUTER CHAIR**

Size:	480 mm x 420 mm x 60 mm Seat with 400 mm x 400 x 60 mm back
Seat and Back martial:	Sold Seasoned sheesham wood with proper closely knit rubber strips with raw cotton filled and on top fitted with 1 <sup>st</sup> quality foam and covered with durable tapestry cloth.
Arms:	Oval shaped high quality durable plastic arms.
Base:	5-Star configuration steel revolving base with adjustable threaded pedestal with proper locking system and fitted with durable load bearing wheels.

#### Note:

### SPECIFICATIONS OF COMPUTER CHAIR (Compliance Sheet)

Sr. #	Functions/ Peripherals	Specifications	Compliance/ Bidder Response
1	Size:	Size:         480 mm x 420 mm x 60 mm Seat with 400 mm x 400 x 60 mm back	
2	Sold Seasoned sheesham wood with properSeat and Backmartial:filled and on top fitted with 1st quality foam and covered with durable tapestry cloth.		
3	Arms:	Oval shaped high quality durable plastic arms.	
4	Base:	5-Star configuration steel revolving base with adjustable threaded pedestal with proper locking system and fitted with durable load bearing wheels.	

#### Note:

### **SPECIFICATIONS OF OFFICE CHAIR**

Size:	500 mm x 480 mm x 60 mm Seat with 3800 mm x 480 x 60 mm back	
Frame:	Solid seasoned sheesham wood frame measuring 75 mm x 40 mm all around, legs measuring 50 mm x 40 mm with legs measuring. The frame must extend above seat at the back upto 300 mm with cross bar of the same shape and size.	
Arms:	Solid seasoned sheesham wood arms measuring 50 mm x 40 mm and 500 mm long and 200 mm high above frame.	
Seat and Back martial:	Sold Seasoned sheesham wood with proper closely knit rubber strips with raw cotton filled and on top fitted with 1 <sup>st</sup> quality foam and covered with durable brown colour high quality leather/rexine.	
Finish and Polish:	High quality sheesham wood colour polish.	
Note:	Sample of Office Chair can be checked from Survey of Pakistan before quoting rates.	

#### Note:

### SPECIFICATIONS OF OFFICE CHAIR (Compliance Sheet)

Sr. #	Functions/ Peripherals		
1	Size:	Size:         500 mm x 480 mm x 60 mm Seat with 3800 mm x 480 x 60 mm back	
2	Frame:	Solid seasoned sheesham wood frame measuring 75 mm x 40 mm all around, legs measuring 50 mm x 40 mm with legs measuring. The frame must extend above seat at the back upto 300 mm with cross bar of the same shape and size.	
3	Solid seasoned sheesham wood armsArms:measuring 50 mm x 40 mm and 500 mmlong and 200 mm high above frame.		
4	Seat and Back martial: Sold Seasoned sheesham wood with proper closely knit rubber strips with raw cotton filled and on top fitted with 1 <sup>st</sup> quality foam and covered with durable brown colour high quality leather/rexine.		
5	Finish and Polish:High quality sheesham wood colour polish.		

#### Note:

Sample of Office Chair can be checked from Survey of Pakistan before quoting rates.

#### Note:

### **SPECIFICATIONS OF UPS 2KVA**

Input Supply:	170 - 270 V (AC), 50/60Hz Auto-Selection, Frequency Converter Mode
Output Supply:	220 - 240 V (AC), 50/60Hz
Power Rating:	2000VA/2000W
Runtime:	5 Minutes with Internal Battery and extended runtime with externally plugged-in battery pack.
Connections:	6xIEC C13 (10A) outlets + 2xIEC C19 (16A). Outlets Serial, USB connectivity and a slot for an optional communication card
Warranty:	12 Months, UPS and Battery (free of cost maintenance and replacement)
After Sale Services:	Battery Maintenance & Replacement, Emergency Service Cover and Preventative Maintenance
Front Panel	Provides schematic overview of critical data for guided operation and troubleshooting on color LCD touch-screen.
Load segment Control:	Proper load segment control to prioritize shutdowns of non-essential devices to increase runtime.
Automatic internal bypass	Pure static bypass switch without bridging contactor securing a fast and reliable transfer to and from bypass, rated for 125% nominal load.
Automatic restart:	After UPS automatic shutdown, automatics restart of the connected equipment upon the return of utility power.
ECO Mode	Operating mode that by-passes unused electrical components in good power conditions to achieve high operating efficiency without sacrificing protection
Input Power Factor Correction:	Input power factor is remains 1 regardless of load and mains voltage.
Intelligent battery Management:	Maximizes battery performance, life, and reliability through intelligent, precision charging.

#### Note:

# SPECIFICATIONS OF UPS 2KVA (Compliance Sheet)

Sr. #	Functions/ Peripherals	Specifications	Compliance/ Bidder Response
1	Input Supply:	170 - 270 V (AC), 50/60Hz Auto-Selection, Frequency Converter Mode	
2	Output Supply:	220 - 240 V (AC), 50/60Hz	
3	Power Rating:	2000VA/2000W	
4	Runtime:	5 Minutes with Internal Battery and extended runtime with externally plugged-in battery pack.	
5	Connections:	6xIEC C13 (10A) outlets + 2xIEC C19 (16A). Outlets Serial, USB connectivity and a slot for an optional communication card	
6	Warranty:	12 Months, UPS and Battery (free of cost maintenance and replacement)	
7	After Sale Services:	Battery Maintenance & Replacement, Emergency Service Cover and Preventative Maintenance	
8	Front Panel	Provides schematic overview of critical data for guided operation and troubleshooting on color LCD touch- screen.	
9	Load segment Control:	Proper load segment control to prioritize shutdowns of non-essential devices to increase runtime.	
10	Automatic internal bypass	Pure static bypass switch without bridging contactor securing a fast and reliable transfer to and from bypass, rated for 125% nominal load.	
11	Automatic restart:	After UPS automatic shutdown, automatics restart of the connected equipment upon the return of utility power.	
12	ECO Mode	Operating mode that by-passes unused electrical components in good power conditions to achieve high operating efficiency without sacrificing protection	

13	Input Power Factor Correction:	Input power factor is remains 1 regardless of load and mains voltage.	
14	Intelligent battery Management:	Maximizes battery performance, life, and reliability through intelligent, precision charging.	

## **SPECIFICATIONS OF PLOTTER 44" SIZE**

Sr. #	Functions / Peripherals	Specifications
1.	Brand	Renowned Brand commonly used in Pakistan
2.	Model size	1118mm
3.	Print speed	180 A1/hr, 19.3 sec/A11
4.	Print resolution	Up to 2400 x 1200 optimized dpi
5.	Nozzle Pitch	1200 dpi (2 lines)
6.	Technology	Thermal / Inkjet
7.	Ink types	Dye-based (C, M, Y, pK, G); Pigment-based (mK)
8.	Ink Droplet Size	5 pl
9.	Print heads	1 universal print head
10.	Line accuracy	±0.1% or less
11.	Minimum line width	0.02 mm (PDF addressable at 1200 dpi);
12.	Handling	Sheet feed, automatic front-loading roll feed, smart roll switching3, integrated output stacker, media bin, automatic horizontal cutter
13.	Standard sheets	A4, A3, A2, A1, A0
14.	E-print Capability	Yes
15.	Media Roll Outer	170 mm
16.	Grammage	60 to 328 g/m²
17.	Thickness	Up to 31.5 mil
18.	memory	128GB
19.	Hard disk 500 GB self-encrypting	
20.	Media Type	Bond And coated paper (bond, coated, heavy weight coated, super heavy weight plus matte) Technical Paper(natural tracing, translucent bond) film(clear comma matte), photographic paper(satin, gloss, semi-gloss, matte, high gloss), backlit, self- adhesive(polypropylene, vinyl), blueprint

21.	Interfaces	Gigabit Ethernet (10/100/1000Base-T), supporting the following standards: TCP/IP, Boot IP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, line printing daemon, Inter printing protocol, NTLM v2, SMBv3, authentication (LEAP, PEAP, EAP-TLS), and wifi.	
22.	Print languages (standard)	PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP- GL/2, HP-RTL, TIFF, JPEG, DWG, CALS G4;	
		Non-PostScript Printer: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4	
23.	Print languages (optional)	Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7	
24.	Printing paths	Direct printing from USB flash drive, print from network shared folder, email printing, driver for latest Windows,	
25.	A0 size drawing print	37 sec	
26.	Non Printable Area(cut- Sheet)	3x17x3x3mm	
27.	Drivers	PostScript Printer: Raster, PostScript and PDF drivers for Windows 10 or later, Non-PostScript Printer: Raster drivers for Windows 10 or later,	
28.	Environmental	ENERGY STAR, ErP, WEEE, ROHS (EU), REACH, EPEAT	
29.	Power Consumption	<100W(printing), <24W(Ready), <0.3W(Sleep) Power cable Round Pin Pakistan compatible	
30.	Warranty	One-year hardware warranty.	
31.	Dealership	Authorized Dealership Gold / Higher with manufactural authorization letter	
32.	Cartridges	One set of extra cartridge	

# SPECIFICATIONS OF PLOTTER 44" SIZE (Compliance Sheet)

Sr. #	Functions / Peripherals	Specifications	Compliance/ Bidder Response
1.	Brand	Renowned Brand commonly used in Pakistan	
2.	Model size	1118mm	
3.	Print speed	180 A1/hr, 19.3 sec/A11	
4.	Print resolution	Up to 2400 x 1200 optimized dpi	
5.	Nozzle Pitch	1200 dpi (2 lines)	
6.	Technology	Thermal / Inkjet	
7.	Ink types	Dye-based (C, M, Y, pK, G); Pigment- based (mK)	
8.	Ink Droplet Size	5 pl	
9.	Print heads	1 universal print head	
10.	Line accuracy	±0.1% or less	
11.	Minimum line width	0.02 mm (PDF addressable at 1200 dpi);	
12.	Handling	Sheet feed, automatic front-loading roll feed, smart roll switching3, integrated output stacker, media bin, automatic horizontal cutter	
13.	Standard sheets	A4, A3, A2, A1, A0	
14.	E-print Capability	Yes	
15.	Media Roll Outer	170 mm	
16.	Grammage	60 to 328 g/m <sup>2</sup>	
17.	Thickness	Up to 31.5 mil	
18.	memory	128GB	
19.	Hard disk	500 GB self-encrypting	
20.	Media Type	Bond And coated paper (bond, coated, heavy weight coated, super heavy weight plus matte) Technical Paper(natural tracing, translucent bond) film(clear comma matte), photographic paper(satin, gloss, semi-gloss, matte, high gloss), backlit, self- adhesive(polypropylene, vinyl), blueprint	

21.		Gigabit Ethernet (10/100/1000Base-T),	
		supporting the following standards:	
		TCP/IP, Boot IP/DHCP (IPv4 only),	
	Interfaces	DHCPv6, TFTP (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS	
	Interfaces	Discovery, line printing daemon, Inter	
		printing protocol, NTLM v2, SMBv3,	
		authentication (LEAP, PEAP, EAP-TLS),	
		and wifi.	
22.	Print languages	PostScript Printer: Adobe PostScript	
	(standard)	3, Adobe PDF 1.7, HP-GL/2, HP-RTL,	
	. ,	TIFF, JPEG, DWG, CALS G4;	
		Non-PostScript Printer: HP-GL/2, HP-	
		RTL, TIFF, JPEG, CALS G4	
23.	Print languages	Non-PostScript Printer: Adobe	
	(optional)	PostScript 3, Adobe PDF 1.7	
24.	Printing paths	Direct printing from USB flash drive,	
		print from network shared folder, email	
		printing, driver for latest Windows,	
25.	A0 size	37 sec	
	drawing print		
26.	Non Printable	3x17x3x3mm	
	Area(cut-		
	Sheet)		
27.	Drivers	PostScript Printer: Raster, PostScript and	
		PDF drivers for Windows 10 or later, Non-	
		PostScript Printer: Raster drivers for	
		Windows 10 or later,	
28.	Environmental	ENERGY STAR, ErP, WEEE, RoHS	
		(EU), REACH, EPEAT	
29.	Power	<100W(printing), <24W(Ready),	
	Consumption	<0.3W(Sleep)	
		Power cable Round Pin Pakistan	
		compatible	
30.	Warranty	One-year hardware warranty.	
31.	Dealership	Authorized Dealership Gold / Higher	
		with manufactural authorization	
		letter	
32.	Cartridges	One set of extra cartridge	
		•	

# **SPECIFICATION OF SCANNER- SIZE (A0) 48"**

Sr. #	Peripherals/Functions	Specifications	
1.	Brand	Renowned Brand commonly used in Pakistan	
2.	Enhanced resolution	9600 dpi	
3.	Optical resolution	1200 x 1200 dpi	
4.	Document Thickness	Max. 2.5 mm (0.1 inch)	
5.	Imaging technology	CIS scanning technology	
6.	Accuracy	± 0.1% ± 1 pixel	
7.	Scan Speed Color	200 dpi - 7.5 inch/s or better	
8.	Scan Speed BW	200 dpi - 15 inch/s or better	
9.	Data capture(color/mono)	48-bit/16-bit gray scale	
10.	Maximum scan width	1220 mm (48 inch)	
11.	Paper Path	Face up, Front entry, Front or rear exit	
12.	Scan direction	± 0.08% across 48 inch scanning width	
13.	Supported file formats	PDF, TIFF, JPEG, JPEG2000, DWF, multi-page PDF generation	
14.	Scan to	File, email, USB, HDD, network folder, FTP, print	
15.	Settings	Type of original-preset, color mode, resolution (dpi), batch, single/multi-page, file format, customizable file naming, customizable default settings, image crop and align preview, enlarge/reduce, blueprint, lightness, saturation and RGB controls, white point and black point adjust, sharpen/blur, background removal, invert, mirror, accounting	
16.	Copier specific settings	Print mode, for printer output destination	
17.	Maximum scan size7	0.91 x 26 m (36 x 1204 in); 0.6 x 37.9 m (24 x 1491 in); 0.3 x 75.8 m (12 x 2991 in)	
18.	Batch	Available with scan and copy	
19.	Preview	Scan, copy and print after previewing the original in the advanced touchscreen controller	
20.	Size detection	Automatic width detection. Manual size selection also possible	
21.	Applications Media	Line drawings, Maps, Office Graphics, Posters, Presentations	
22.	Handling	Straight-through scan paper path for sheet and cardboard originals. Face-up, front entry, rear exit, rewind to front, use document return guide for front- return	
23.	Туреѕ	Non-abrasive paper, sepia, blueprints, plastic, plastic laminate, foam board, cardboard, newspaper	
24.	Processor	Intel Core i7 or latest	
25.	Memory	4 GB memory, 500 GB hard disk or more	
26.	Connectivity	Dual Gigabit Ethernet (1000 Base-T), Hi-Speed USB 3.0 certified	

27.	Drivers (included)	Windows 10 version drivers for compatible HP Page Wide XL and HP Design Jet Printers	
28.	User Interface	15.6-inch (396-mm) large touchscreen to preview and enhance images	
29.	Software	Scanning software compatible with windows 10	
30.	Calibration Sheet &	Calibration Sheet along with calibration software	
	Software		
31.	Stand	Standard brand specific Stand	
32.	Power Requirements	Input voltage (auto rang Ving): 240 VAC (± 10%), 50/60	
		Hz, 5 A max, or Pakistan Compatible	
33.	Warranty	01 Year on site comprehensive	
34.	Dealership	Authorized Dealership Gold / Higher with manufactural	
		authorization letter	

# SPECIFICATION OF SCANNER- SIZE (A0) 48" (Compliance Sheet)

Sr. #	Peripherals/Functions	Specifications	Compliance/ Bidder Response
1.	Brand	Renowned Brand commonly used in Pakistan	
2.	Enhanced resolution	9600 dpi	
3.	Optical resolution	1200 x 1200 dpi	
4.	Document Thickness	Max. 2.5 mm (0.1 inch)	
5.	Imaging technology	CIS scanning technology	
6.	Accuracy	± 0.1% ± 1 pixel	
7.	Scan Speed Color	200 dpi - 7.5 inch/s or better	
8.	Scan Speed BW	200 dpi - 15 inch/s or better	
9.	Data capture(color/mono)	48-bit/16-bit gray scale	
10.	Maximum scan width	1220 mm (48 inch)	
11.	Paper Path	Face up, Front entry, Front or rear exit	
12.	Scan direction	± 0.08% across 48 inch scanning width	
13.	Supported file formats	PDF, TIFF, JPEG, JPEG2000, DWF, multi-page PDF generation	
14.	Scan to	File, email, USB, HDD, network folder, FTP, print	
15.	Settings	Type of original-preset, color mode, resolution (dpi), batch, single/multi- page, file format, customizable file naming, customizable default settings, image crop and align preview, enlarge/reduce, blueprint, lightness, saturation and RGB controls, white point and black point adjust, sharpen/blur, background removal, invert, mirror, accounting	
16.	Copier specific settings	Print mode, for printer output destination	
17.	Maximum scan size7	0.91 x 26 m (36 x 1204 in); 0.6 x 37.9 m (24 x 1491 in); 0.3 x 75.8 m (12 x 2991 in)	

18.	Batch	Available with scan and copy	
19.	Preview	Scan, copy and print after previewing the original in the advanced touchscreen controller	
20.	Size detection	Automatic width detection. Manual size selection also possible	
21.	Applications Media	Line drawings, Maps, Office Graphics, Posters, Presentations	
22.	Handling	Straight-through scan paper path for sheet and cardboard originals. Face- up, front entry, rear exit, rewind to front, use document return guide for front-return	
23.	Types	Non-abrasive paper, sepia, blueprints, plastic, plastic laminate, foam board, cardboard, newspaper	
24.	Processor	Intel Core i7 or latest	
25.	Memory	4 GB memory, 500 GB hard disk or more	
26.	Connectivity	Dual Gigabit Ethernet (1000 Base-T), Hi-Speed USB 3.0 certified	
27.	Drivers (included)	Windows 10 version drivers for compatible HP Page Wide XL and HP Design Jet Printers	
28.	User Interface	15.6-inch (396-mm) large touchscreen to preview and enhance images	
29.	Software	Scanning software compatible with windows 10	
30.	Calibration Sheet & Software	Calibration Sheet along with calibration software	
31.	Stand	Standard brand specific Stand	
32.	Power Requirements	Input voltage (auto rang Ving): 240 VAC (± 10%), 50/60 Hz, 5 A max, or Pakistan Compatible	
1			

		comprehensive	
34.	Dealership	Authorized Dealership Gold	
		/ Higher with manufactural	
		authorization letter	

# **SPECIFICATION OF PHOTOCOPIER**

Sr. #	MAIN UNIT	Specifications	
1.	ТҮРЕ	Monochrome Laser Multifunctional	
2.		Standard: Print, Copy, Scan, Send, Store	
	CORE FUNCTIONS	Optional: Fax	
3.	PROCESSOR	Dual Custom Processor (Shared)	
4.	CONTROL PANEL	10.1" TFT LCD WSVGA Color Touch-panel	
5.	MEMORY	RAM 2 GB or higher	
6.		Standard: 250 GB	
	HARD DISK DRIVE	Maximum: 1 TB	
7.		Optional (250 GB, 1 TB)	
	MIRRORING HARD DISK DRIVE	Method: Raid1	
8.	PRINT RESOLUTION	1200 dpi x 1200 dpi	
9.		Network	
		Standard: 1000Base-T/100Base-TX/10Base-T,	
		Built Wifi	
	INTERFACE CONNECTION	Optional: NFC, Bluetooth	
		Other, Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),	
		USB 2.0 x1 (Device)	
		Optional: Serial Interface, Copy Control Interface	
10.	PAPER CAPACITY (LTR, 20LB BOND)	Standard: 1,180 Sheets Maximum: 6,330 Sheets	
11.		Standard: Two 550-sheet Paper Cassettes, 80-sheet	
		Stack Bypass	
	PAPER SOURCES (LTR, 20LB	Optional: Two 550-sheet Paper Cassettes (Cassette	
	BOND)	Feeding Unit-AN1), 2,450-sheet Paper Deck (High	
		Capacity Cassette Feeding Unit-B1), 2,700-sheet	
		Paper Deck (Paper Deck Unit-F1)	
12.	PAPER OUTPUT CAPACITY	Standard: 250 Sheets	
	(LTR, 20LB BOND)	Maximum: 3,350 Sheets (with External Finishers)	
13.		Standard: Collate, Group	
		With Inner Finisher: Collate, Group, Offset, Staple,	
	FINISHING CAPABILITIES	Hole Punch,1 Staple-Free Staple, Staple On Demand	
	FINISHING CAPABILITIES	With External Finisher: Collate, Group, Offset, Staple,	
		Booklet,2 Staple-Free Staple, Staple On Demand, Hole	
		Punch3	
14.		Paper Cassettes: Thin, Plain, Recycled, Color, Heavy,	
	SUPPORTED MEDIA TYPES	Pre-punched	
		Stack Bypass: Thin, Plain, Recycled, Color, Heavy, Pre-	
		punched, Bond, Transparency, Label, Envelope	
15.		Paper Cassette (1): Legal, Letter, Letter-R, Executive,	
		Statement-R, Custom Size (5-1/2" x 7-1/8" to 11-3/4"	
		x 15-3/8")	
	SUPPORTED MEDIA SIZES	Paper Cassette (2): 11" x 17", Legal, Letter, Letter-R,	
		Executive, Statement-R, Custom Size (5-1/2" x 7-1/8"	
		to 11-3/4" x 15-3/8") Stack Bypass: 11" x 17", Legal,	
		Letter, Letter-R, Executive, Statement-R, Envelope	

		[No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 5-7/8" to 11-3/4" x 17")	
16.		Paper Drawers: Paper Cassettes: 16 lb. Bond to 34 lb. Bond (60 to 128 g/m2)	
	SUPPORTED MEDIA WEIGHTS	Stack Bypass: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m2)	
		Duplexing: 16 lb. Bond to 28 lb. Cover (60 to 105 g/m2)	
17.	WARM-UP TIME	From Power On: 24 Seconds or Less From Deep Sleep Mode: 10 Seconds or Less Quick Startup Mode: 4 Seconds4	
18.	DIMENSIONS (W X D X H)	23-1/8" x 29-1/8" x 47" (587 mm x 740 mm x 1,193 mm)5	
19.	INSTALLATION SPACE (WXD)	Basic [With ADF (Stack Bypass and Cassette Drawers Open)]: 35" x 46-1/2" (889 mm x 1,182 mm) Fully Configured [With ADF+Paper Deck Unit-F1+ Booklet Finisher-Y1 (Cassette Drawers Open)]: 71-	
20.	WEIGHT	3/8" x 50-3/8" (1,811 mm x 1,280 mm) Approx. 240.7 lb. (109.2 kg)6	
		INT SPECIFICATIONS	
21.	PRINT SPEED	Up to 45 ppm (Letter); Up to 32 ppm (Letter-R); Up to 25 ppm (Legal); Up to 22 ppm (11" x 17")	
22.	STANDARD PAGE DESCRIPTION LANGUAGES	UFR II, PCL®6, Adobe® PS® 3	
23.	DIRECT PRINT	Available from USB, Advanced Box, Remote UI, and Web Access (Opt.)7	
24.	SUPPORTED FILE TYPES FOR DIRECT PRINT	PDF, TIFF, JPEG, EPS, XPS	
25.	PRINTING FROM MOBILE AND CLOUD	A range of software and MEAP-based solutions are available to provide printing from mobile devices or Internet-connected devices and cloud-based services depending on your requirements.	
26.	FONTS	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese),8 Barcode Fonts9 PS fonts: 136 Roman	
27.		UFRII: Windows Vista <sup>®</sup> /Server 2008/Windows <sup>®</sup> 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later)	
	OPERATING SYSTEM10	PCL: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10 PS: Windows Vista/Server 2008/Windows 7/Server 2008 R2/Windows 8/Server 2012/Windows 8.1/Server 2012 R2/Windows 10, MAC OS X (10.6.8 or later)	

	I	
		PPD: MAC OS 9.1 or later, MAC OS X (10.3.9 or
		later), Windows Vista/Windows 7/Windows
		8/Windows 8.1/Windows 10
28.		Suspend Job Timeout, Subset Finishing (PS only),
		Profile Settings, Secured Print, Forced Hold Printing,
		Watermark, Page Border, Header/Footer, Page
	PRINT FEATURES	Layout, Two-sided Printing, Collating, Booklet
		Printing, Grouping, Mixed Paper Sizes/Orientations,
		Offsetting, Printing on Transparencies, Front/Back
		Covers, Toner Reduction, Poster Printing
	CC	DPY SPECIFICATIONS
29.		Up to 45 ppm (Letter); Up to 32 ppm (Letter-R); Up
	COPY SPEED	to 25 ppm (Legal); Up to 22 ppm (11" x 17")
30.	FIRST-COPY-OUT-TIME	As fast as 3.8 seconds
31.		Reading: Up to 600 dpi x 600 dpi
	COPY RESOLUTION	Printing: 1200 dpi x 1200 dpi
32.	MULTIPLE COPIES	Up to 999 copies
33.	COPY EXPOSURE	Automatic or Manual (9 Levels)
34.	MAGNIFICATION	25%-400% (1% Increments)
35.	PRESET REDUCTIONS	25%, 50%, 64%, 73%, 78%
36.	PRESET ENLARGEMENTS	121%, 129%, 200%, 400%
37.		Preset Reduction/Enlargement Ratios by Area,
		Paper Setting, Previous Settings, Favorite Settings,
	BASIC COPY FEATURES	Finishing, Two-Sided, Density Adjustment, Original
		Type Selection, Interrupt Mode, Setting
		Confirmation/Cancel
38.		Book to Two Pages, Two-sided Original, Finishing,
		Booklet, Job Build, N on 1, Add Cover, Insert Sheets,
		Different Size Originals, Density Adjustment, Original
		Type Selection, Transparency Cover Sheets, Page
	SPECIAL COPY FEATURES	Numbering, Copy Set Numbering, Sharpness, Erase
		Frame, Secure Watermark, Print Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge
		Job Blocks, Job Done Notice, Mirror Image, Store in Mail
		Box, Superimpose Image, Copy ID Card, Detect Feeder
		Multi Sheet Feed, Free Size Original
	SC	AN SPECIFICATIONS
39.	T/D5	Standard Single Pass Duplexing Automatic
	ТҮРЕ	Document Feeder
40.	DOCUMENT FEEDER PAPER	Single Pass DADF-A1: 150 Sheets (20 lb. Bond)
	CAPACITY	DADF-AV1: 100 Sheets (20 lb. Bond)
41.	DOCUMENT FEEDER	11" x 17", Legal, Letter, Letter-R, Statement,
	SUPPORTED MEDIA SIZES	Statement-R
42.		Single Pass DADF-A1
		BW Original: 13 lb. Bond to 58 lb. Cover (50 to 157
	DOCUMENT FEEDER	g/m2)
	SUPPORTED MEDIA WEIGHT	CL Original: 17 lb. Bond to 58 lb. Cover (64 to 157
		g/m2)
		DADF-AV1
	1	

		DW/ Original, 12 lb Dand to 24 lb Dand /50 to 120	
		BW Original: 13 lb. Bond to 34 lb. Bond (50 to 128 g/m2)	
		CL Original: 17 lb. Bond to 34 lb. Bond (64 to 128 g/m2)	
43.	PLATEN ACCEPTABLE ORIGINALS	Sheet, Book, 3-Dimensional Objects [Up to 4.4 lb. (2 kg)]	
44.		Color Network ScanGear2 for both Twain and WIA	
	PULL SCAN	Supported OS: Windows Vista/7/8/8.1/10 Windows Server 2008/Server 2008 R2/Server 2012/Server 2012 R2	
45.	SCAN RESOLUTION	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100dpi	
46.	SCAN TO MOBILE DEVICES AND CLOUD-BASED SERVICES	A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.	
47.		Single Pass DADF-A1 Single-sided Scanning (BW): 80 ipm (300 dpi)/80 ipm (600 dpi)	
	SCAN SPEED (LETTER)	Single-sided Scanning (Color): 80 ipm (300 dpi)/60 ipm (600 dpi)	
		Double-sided Scanning (BW): 160 ipm (300 dpi)/150 ipm (600 dpi)	
		Double-sided Scanning (Color): 160 ipm (300 dpi)/80 ipm (600 dpi)	
		DADF-AV1	
		Single-sided Scanning (BW): 70 ipm (300 dpi)/51 ipm (600 dpi)	
		Single-sided Scanning (Color): 70 ipm (300 dpi)/51 ipm (600 dpi)	
		Double-sided Scanning (BW): 35 ipm (300 dpi)/25.5 ipm (600 dpi)	
		Double-sided Scanning (Color): 35 ipm (300 dpi)/25.5 ipm (600 dpi)	
	SEI	ND SPECIFICATIONS	
48.	DESTINATION	E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)	
49.	COLOR MODE	Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and- White), Full color, Grayscale, and Black-and-White	
50.	ADDRESS BOOK	Automatic-Color Select (Full Color/Grayscale), Automatic-Color Select (Full Color/Black-and- White), Full color, Grayscale, and Black-and-White	
51.	SEND RESOLUTION	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100dpi	
52.	COMMUICATION PROTOCOL	File: FTP, SMB v3.0, WebDAV	
		· · · · · · · · · · · · · · · · · · ·	

		E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)	
53.	FILE FORMAT	Standard: TIFF, JPEG, PDF(Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b), XPS (Compact, Searchable), Office Open XML (PowerPoint <sup>®</sup> , Word)	
		Optional: PDF (Trace & Smooth, Encrypted), PDF/XPS (Digital Signature)	
54.	UNIVERSAL SEND FEATURES	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Finished Stamp, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Detect Feeder Multi Sheet Feed	
	FA	X SPECIFICATIONS	
55.	MAXIMUM NUMBER OF LINES	4	
56.	MODEM SPEED	Super G3: 33.6 Kbps G3: 14.4 Kbps	
57.	COMPRESSION METHOD	MH, MR, MMR, JBIG	
58.	RESOLUTION	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi	
59.	SENDING / RECORDING SIZE	Statement-R to 11" x 17"	
60.	FAX MEMORY	Up to 30,000 pages	
61.	SPEED DIALS	Max. 200	
62.	GROUP DIALS / DESTINATIONS	Max. 199 dials	
63.	SEQUENTIAL BROADCAST	Max. 256 addresses	
64.	MEMORY BACKUP	Yes	
65.	FAX FEATURES	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed	
	STC	RE SPECIFICATIONS	
66.	MAIL BOX (NUMBER SUPPORTED)	100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored	
67.	ADVANCED BOX	Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10) Concurrent Connections (Max.) SMB: 64 WebDAV: 3 (Active Sessions)	

68.	ADVANCED BOX AVAILABLE	Approx. 16 GB (Standard HDD)		
	DISC SPACE	Approx. 480 GB (1 TB HDD)		
69.	ADVANCED BOX FEATURES	Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support		
70.	MEMORY MEDIA	Standard: USB		
	SEC	URITY SPECIFICATIONS		
71. AUTHENTICATION		Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in		
		Optional: uni FLOW		
72.	DATA	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated)		
		Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)		
73.	NETWORK	Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP		
74.		Standard: Secure Print, Forced Hold Printing, Adobe LiveCycle® Rights Management ES2.5 Integration		
	DOCUMENT	Optional: Encrypted PDF, Encrypted Secure Print, User and Device signatures, Secure Watermarks, Document Scan Locking		
	ENVIRO	NMENTAL SPECIFICATIONS		
75.		Temperature: 50 to 86°F		
	OPERATING ENVIRONMENT	Humidity: 20 to 80% RH (no condensation)		
76.	POWER REQUIREMENTS	120-127 V AC, 60 Hz, 9.3A		
77.	PLUG (MAIN UNIT)	NEMA 5-15P		
78.		Maximum Approx. 1.5 kWh		
		Standby: Approx. 38 W		
	POWER CONSUMPTION	Sleep Mode: Approx. 0.9 W11		
		Typical Electricity Consumption (TEC) Rating: 2.2 kWh		
		ENERGY STAR <sup>®</sup> Certified		
79.		ENERGI STAR CERtined		
79.	STANDARDS	Rated EPEAT® Gold12		
79.	STANDARDS			
79.	STANDARDS Toner Life	Rated EPEAT <sup>®</sup> Gold12		

82.	Warranty	One-years hardware warranty.	
83.	Dealership	Authorized Dealership Gold / Higher with	
		manufactural authorization letter	

# SPECIFICATION OF PHOTOCOPIER (Compliance Sheet)

Sr. #	MAIN UNIT	Specifications	Compliance/ Bidder Response
1.	ТҮРЕ	Monochrome Laser Multifunctional	
2.	CORE FUNCTIONS	Standard: Print, Copy, Scan, Send, Store Optional: Fax	
3.	PROCESSOR	Dual Custom Processor (Shared)	
4.	CONTROL PANEL	10.1" TFT LCD WSVGA Color Touch-panel	
5.	MEMORY	RAM 2 GB or higher	
6.		Standard: 250 GB	
	HARD DISK DRIVE	Maximum: 1 TB	
7.	MIRRORING HARD	Optional (250 GB, 1 TB)	
	DISK DRIVE	Method: Raid1	
8.	PRINT RESOLUTION	1200 dpi x 1200 dpi	
9.		Network Standard: 1000Base-T/100Base- TX/10Base-T, Built Wifi	
	INTERFACE	Optional: NFC, Bluetooth	
	CONNECTION	Other, Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Optional: Serial Interface, Copy Control Interface	
10.	PAPER CAPACITY (LTR, 20LB BOND)	Standard: 1,180 Sheets Maximum: 6,330 Sheets	
11.	PAPER SOURCES (LTR, 20LB BOND)	Standard: Two 550-sheet Paper Cassettes, 80-sheet Stack Bypass Optional: Two 550-sheet Paper Cassettes (Cassette Feeding Unit- AN1), 2,450-sheet Paper Deck (High Capacity Cassette Feeding Unit-B1), 2,700-sheet Paper Deck (Paper Deck Unit-F1)	
12	PAPER OUTPUT	Standard: 250 Sheets	

	CAPACITY (LTR, 20LB	Maximum: 3,350 Sheets (with	
	BOND)	External Finishers)	
13.		Standard: Collate, Group	
		With Inner Finisher: Collate, Group, Offset, Staple, Hole	
	FINISHING CAPABILITIES	Punch,1 Staple-Free Staple, Staple On Demand	
		With External Finisher: Collate, Group, Offset, Staple,	
		Booklet,2 Staple-Free Staple, Staple On Demand, Hole Punch3	
14.		Paper Cassettes: Thin, Plain, Recycled, Color, Heavy, Pre- punched	
	SUPPORTED MEDIA TYPES	Stack Bypass: Thin, Plain, Recycled, Color, Heavy, Pre- punched, Bond, Transparency, Label, Envelope	
15.		Paper Cassette (1): Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (5-1/2" x 7-1/8" to 11-3/4" x 15-3/8")	
	SUPPORTED MEDIA SIZES	Paper Cassette (2): 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (5-1/2" x 7-1/8" to 11-3/4" x 15-3/8")	
		Stack Bypass: 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Custom Size (3-7/8" x 5-7/8" to	
		11-3/4" x 17")	
16.	SUPPORTED MEDIA	Paper Drawers: Paper Cassettes: 16 lb. Bond to 34 lb. Bond (60 to 128 g/m2)	
	WEIGHTS	Stack Bypass: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m2) Duplexing: 16 lb. Bond to 28 lb.	
		Cover (60 to 105 g/m2)	
17.		From Power On: 24 Seconds or Less	
	WARM-UP TIME	From Deep Sleep Mode: 10 Seconds or Less	
		Quick Startup Mode: 4 Seconds4	
18.	DIMENSIONS (W X D X H)	23-1/8" x 29-1/8" x 47" (587 mm x 740 mm x 1,193 mm)5	
19.	INSTALLATION SPACE	Basic [With ADF (Stack Bypass	

	(WXD)	and Cassette Drawers Open)]: 35" x 46-1/2" (889 mm x 1,182	
		mm)	
		Fully Configured [With	
		ADF+Paper Deck Unit-F1+	
		Booklet Finisher-Y1 (Cassette	
		Drawers Open)]: 71-3/8" x 50-	
		3/8" (1,811 mm x 1,280 mm)	
20	WEIGHT		
20.		Approx. 240.7 lb. (109.2 kg)6 PECIFICATIONS	
	PRINT SI	CIFICATIONS	
21.		Up to 45 ppm (Letter); Up to 32	
		ppm (Letter-R); Up to 25 ppm	
	PRINT SPEED	(Legal); Up to 22 ppm (11" x	
		17")	
22.	STANDARD PAGE		
	DESCRIPTION	UFR II, PCL <sup>®</sup> 6, Adobe <sup>®</sup> PS <sup>®</sup> 3	
	LANGUAGES		
23.		Available from USB, Advanced	
	DIRECT PRINT	Box, Remote UI, and Web	
		Access (Opt.)7	
24	SUPPORTED FILE		
27.	TYPES FOR DIRECT	PDF, TIFF, JPEG, EPS, XPS	
	PRINT	ι Δι, Πιι, Jr LO, Lr J, Λr J	
25.		A range of software and MEAP-	
25.		based solutions are available to	
	PRINTING FROM	provide printing from mobile	
	MOBILE AND CLOUD	devices or Internet-connected	
		devices and cloud-based	
		services depending on your	
		requirements.	
26.		PCL fonts: 93 Roman, 10	
		Bitmap fonts, 2 OCR fonts,	
		Andalé Mono WT J/K/S/T	
	FONTS	(Japanese, Korean, Simplified	
		and Traditional	
		Chinese),8 Barcode Fonts9	
		PS fonts: 136 Roman	
27.		UFRII: Windows Vista <sup>®</sup> /Server	
		2008/Windows® 7/Server 2008	
		R2/Windows 8/Server	
		2012/Windows 8.1/Server	
	OPERATING	2012 R2/Windows 10, MAC OS	
	SYSTEM10	X (10.6.8 or later)	
	STSTEIVILU		
		PCL: Windows Vista/Server	
		2008/Windows 7/Server 2008	
		R2/Windows 8/Server	
		2012/Windows 8.1/Server	

2012 R2/Windows 10PS: Windows Vista/Server2008/Windows 7/Server 2008R2/Windows 8/Server2012/Windows 8.1/Server	
2008/Windows 7/Server 2008 R2/Windows 8/Server	
R2/Windows 8/Server	
2012/Windows 8.1/Server	
2012 R2/Windows 10, MAC OS	
X (10.6.8 or later)	
PPD: MAC OS 9.1 or later, MAC	
OS X (10.3.9 or later), Windows	
Vista/Windows 7/Windows	
8/Windows 8.1/Windows 10	
28. Suspend Job Timeout, Subset	
Finishing (PS only), Profile	
Settings, Secured Print, Forced	
Hold Printing, Watermark, Page	
Border, Header/Footer, Page	
PRINT FEATURES Layout, Two-sided Printing,	
Collating, Booklet Printing,	
Grouping, Mixed Paper	
Sizes/Orientations, Offsetting,	
Printing on Transparencies,	
Front/Back Covers, Toner	
Reduction, Poster Printing	
COPY SPECIFICATIONS	
29. Up to 45 ppm (Letter); Up to 32	
COPY SPEED ppm (Letter-R); Up to 25 ppm	
(Legal); Up to 22 ppm (11" x	
17")	
30. FIRST-COPY-OUT- As fast as 3.8 seconds	
IIME	
31. Reading: Up to 600 dpi x 600	
COPY RESOLUTION dpi	
Printing: 1200 dpi x 1200 dpi	
32. MULTIPLE COPIES Up to 999 copies	
<sup>33.</sup> COPY EXPOSURE Automatic or Manual (9 Levels)	
MAGNIFICATION 25%-400% (1% Increments)	
<sup>35.</sup> PRESET REDUCTIONS 25%, 50%, 64%, 73%, 78%	
36. PRESET	
121% 129% 200% 400%	
ENLARGEMENTS	
37. Preset Reduction/Enlargement	
BASIC COPY Ratios by Area, Paper Setting,	
FEATURES Previous Settings, Favorite	
Settings, Finishing, Two-Sided,	

		Density Adjustment Original	
		Density Adjustment, Original	
		Type Selection, Interrupt	
		Mode, Setting	
		Confirmation/Cancel	
38.		Book to Two Pages, Two-sided	
		Original, Finishing, Booklet, Job	
		Build, N on 1, Add Cover, Insert	
		Sheets, Different Size Originals,	
		Density Adjustment, Original Type	
		Selection, Transparency Cover	
		Sheets, Page Numbering, Copy Set	
	SPECIAL COPY	Numbering, Sharpness, Erase	
	FEATURES	Frame, Secure Watermark, Print	
		Date, Shift, Gutter, Print & Check, Negative/Positive, Repeat Images,	
		Merge Job Blocks, Job Done	
		Notice, Mirror Image, Store in	
		Mail Box, Superimpose Image,	
		Copy ID Card, Detect Feeder Multi	
		Sheet Feed, Free Size Original	
		PECIFICATIONS	
	SCANSI		
39.		Standard Single Pass Duplexing	
	ТҮРЕ	Automatic Document Feeder	
40.		Single Pass DADF-A1: 150	
	DOCUMENT FEEDER	Sheets (20 lb. Bond) DADF-AV1:	
	PAPER CAPACITY	100 Sheets (20 lb. Bond)	
41.	DOCUMENT FEEDER		
	SUPPORTED MEDIA	11" x 17", Legal, Letter, Letter-	
	SIZES	R, Statement, Statement-R	
42.		Single Pass DADF-A1	
		BW Original: 13 lb. Bond to 58	
		lb. Cover (50 to 157 g/m2)	
		CL Original: 17 lb. Bond to 58	
	DOCUMENT FEEDER	5	
	SUPPORTED MEDIA	lb. Cover (64 to 157 g/m2)	
	WEIGHT	DADF-AV1	
		BW Original: 13 lb. Bond to 34	
		lb. Bond (50 to 128 g/m2)	
		CL Original: 17 lb. Bond to 34	
		lb. Bond (64 to 128 g/m2)	
43.	PLATEN ACCEPTABLE	Sheet, Book, 3-Dimensional	
	ORIGINALS	Objects [Up to 4.4 lb. (2 kg)]	
44.	-	Color Network ScanGear2 for	
		both Twain and WIA	
		Supported OS: Windows	
	PULL SCAN	Vista/7/8/8.1/10 Windows	
		Server 2008/Server 2008	
		R2/Server 2012/Server 2012 R2	

45.	SCAN RESOLUTION	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi, 150 x 150 dpi, 100 x 100dpi	
46.	SCAN TO MOBILE DEVICES AND CLOUD-BASED SERVICES	A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.	
47.		Single Pass DADF-A1	
	SCAN SPEED (LETTER)	Single-sided Scanning (BW): 80 ipm (300 dpi)/80 ipm (600 dpi) Single-sided Scanning (Color): 80 ipm (300 dpi)/60 ipm (600 dpi) Double-sided Scanning (BW): 160 ipm (300 dpi)/150 ipm (600 dpi) Double-sided Scanning (Color): 160 ipm (300 dpi)/80 ipm (600 dpi)	
		DADF-AV1	
		Single-sided Scanning (BW): 70 ipm (300 dpi)/51 ipm (600 dpi) Single-sided Scanning (Color): 70 ipm (300 dpi)/51 ipm (600 dpi) Double-sided Scanning (BW): 35 ipm (300 dpi)/25.5 ipm (600 dpi) Double-sided Scanning (Color): 35	
	SEND SE	ipm (300 dpi)/25.5 ipm (600 dpi) PECIFICATIONS	
48.	DESTINATION	E-mail/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box, Super G3 Fax (Optional), IP Fax (Optional)	
49.	COLOR MODE	Automatic-Color Select (Full Color/Grayscale), Automatic- Color Select (Full Color/Black- and-White), Full color, Grayscale, and Black-and- White	
50.	ADDRESS BOOK	Automatic-Color Select (Full Color/Grayscale), Automatic- Color Select (Full Color/Black- and-White), Full color, Grayscale, and Black-and- White	
51.	SEND RESOLUTION	600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi,	

		150 x 150 dpi, 100 x 100dpi	
52.			
52.	COMMUICATION	File: FTP, SMB v3.0, WebDAV	
	PROTOCOL	E-mail/I-Fax: SMTP, POP3, I-Fax (Simple, Full)	
53.		Standard: TIFF, JPEG,	
		PDF(Compact, Searchable, Apply policy, Optimize for Web,	
		PDF A/1-b), XPS (Compact,	
	FILE FORMAT	Searchable), Office Open XML (PowerPoint <sup>®</sup> , Word)	
		Optional: PDF (Trace &	
		Smooth, Encrypted), PDF/XPS	
54.		(Digital Signature) Original Type Selection,Two-	
		sided Original, Book to Two	
		Pages, Different-size Originals, Density Adjustment,	
		Sharpness, Copy Ratio, Erase	
	UNIVERSAL SEND FEATURES	Frame, Job Build, Delayed Send, Preview, Finished Stamp,	
		Job Done Notice, File Name,	
		Subject/Message, Reply-to, E-	
		mail Priority, TX Report, Original Content Orientation,	
		Skip Blank Originals, Detect	
	FAX SP	Feeder Multi Sheet Feed	
55.	MAXIMUM NUMBER OF LINES	4	
56.		Super G3: 33.6 Kbps	
	MODEM SPEED	G3: 14.4 Kbps	
57.	COMPRESSION METHOD	MH, MR, MMR, JBIG	
58.	RESOLUTION	400 x 400 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi	
59.	SENDING / RECORDING SIZE	Statement-R to 11" x 17"	
60.	FAX MEMORY	Up to 30,000 pages	
61.	SPEED DIALS	Max. 200	
62.	GROUP DIALS / DESTINATIONS	Max. 199 dials	

63.	SEQUENTIAL BROADCAST	Max. 256 addresses	
64.	MEMORY BACKUP	Yes	
65.	FAX FEATURES	Original Type Selection, Two- sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Specifying the Sender's Name (when sending fax), Sender's Name (TTI), Select Line, Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Finished Stamp, Job Done Notice, TX Report, Detect Feeder Multi Sheet Feed	
	STORE S	PECIFICATIONS	
66.	MAIL BOX (NUMBER SUPPORTED)	100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored	
67.		Communication Protocol: SMB or WebDAV Supported Client PC: Windows (Windows Vista/7/8/8.1/10)	
	ADVANCED BOX	Concurrent Connections (Max.)	
		SMB: 64	
		WebDAV: 3 (Active Sessions)	
68.	ADVANCED BOX AVAILABLE DISC	Approx. 16 GB (Standard HDD)	
	SPACE	Approx. 480 GB (1 TB HDD)	
69.	ADVANCED BOX FEATURES	Disabling Advanced Box, Storage Filtering, Authentication for Advanced Box Log-in, Search Function, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support	
70.	MEMORY MEDIA	Standard: USB	
	SECURITY	SPECIFICATIONS	

1		
71.	AUTHENTICATION	Standard: Universal Login Manager, User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in
		Optional: uni FLOW
72.	DATA	Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption(FIPS140-2 Validated) Optional: Hard Disk Drive Mirroring, Hard Disk Drive removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)
70		
73.	NETWORK	Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP
74.	DOCUMENT	Standard: Secure Print, ForcedHold Printing, Adobe LiveCycle®Rights Management ES2.5IntegrationOptional: Encrypted PDF,Encrypted Secure Print, User andDevice signatures, SecureWatermarks, Document ScanLocking
	ENVIRONMEN	TAL SPECIFICATIONS
75.	OPERATING	Temperature: 50 to 86ºF
	ENVIRONMENT	Humidity: 20 to 80% RH (no condensation)
76.	POWER REQUIREMENTS	120-127 V AC, 60 Hz, 9.3A
77.	PLUG (MAIN UNIT)	NEMA 5-15P
78.		Maximum Approx. 1.5 kWh
	POWER CONSUMPTION	Standby: Approx. 38 W
		Sleep Mode: Approx. 0.9 W11
		Typical Electricity Consumption (TEC) Rating: 2.2 kWh

79.		ENERGY STAR <sup>®</sup> Certified	
	STANDARDS	Rated EPEAT <sup>®</sup> Gold12	
		RoHS Compliant	
	CON	SUMABLES	
80.	Toner Life	30,000 Copies (OEM Warranted)	
81.	Drum Life	168,000 Copies (OEM Warranted)	
82.	Warranty	One-years hardware warranty.	
83.	Dealership	Authorized Dealership Gold / Higher with manufactural authorization letter	

The document enlists all requirements in left columns. The bidder shall provide his consent in the rightmost column. The response should be explicit in well-defined specification offered for the components against each row. Any ambiguous and implicit words or quotations (such as **yes, ok**, **offered, available and provided etc.**) shall be treated as "non-responsive".

## **SPECIFICATION OF LED TV 110"**

Sr. #	Description of Peripherals	Specifications
1.	Brand	Panasonic/Sony/Samsung etc.
2.	Series	5 Series
3.	Туре	LED TV
4.	Screen Type	Flat Screen
5.	Design	One Design (High Glossy)
6.	Bezel Width	0.5" Thin

7.	Stand Type (Color)	Square	
8.	Screen Size	110" Measured Diagonally	
9.	Resolution	1920 x 1080	
10.	Motion Rate*	60*Motion Rate replaces Clear Motion Rate as the Samsung measure of motion clarity	
11.	Dolby	Dolby Digital Plus / Dolby Pulse	
12.	Sound Effect	SRS Theater Sound HD	
13.	DTS Premium Sound	DTS 2.0 + Digital Out	
14.	Sound Output (RMS)	10W x 2	
15.	Speaker Type	Down Firing + Full Range	
16.	ConnectShare™	Movie	
17.	OSD Language	English, Spanish, French	
18.	Accessories	Closed Captioning, Game Mode, Eco Sensor, Auto Power Off, Clock & On/Off Timer	
19.	HDMI	2	
20.	USB	Yes	
21.	Component	1	
22.	Composite In (AV)	1 (Common Use for Component Y)	
23.	RF In (Terrestrial/Cable Input)	1	
24.	Digital Audio Out (Optical)	1	
25.	Audio Out (Mini Jack)	1	
26.	RS232C	Yes	
27.	Digital Broadcasting	ATSC / Clear QAM	
28.	Power Supply (V)	AC110-240V 60Hz	
29.	Remote	Standard Remote Control (TM1240)	
30.	Stand	Mini Wall Mount Compatibility	
31.	Vesa Wall Mount Compatibility	Yes (200 x 200)	

32.	Power Cable	Yes
33.	User Manual	Yes
34.	Warranty	01 years on site comprehensive

# SPECIFICATION OF LED TV 110" (Compliance Sheet)

Sr. #	Description of Peripherals	Specifications	Compliance/ Bidder Response
1.	Brand	Panasonic/Sony/Samsung etc.	
2.	Series	5 Series	
3.	Туре	LED TV	
4.	Screen Type	Flat Screen	
5.	Design	One Design (High Glossy)	
6.	Bezel Width	0.5" Thin	
7.	Stand Type (Color)	Square	
8.	Screen Size	110" Measured Diagonally	
9.	Resolution	1920 x 1080	
10.	Motion Rate*	60*Motion Rate replaces Clear Motion Rate as the Samsung measure of motion clarity	
11.	Dolby	Dolby Digital Plus / Dolby Pulse	
12.	Sound Effect	SRS Theater Sound HD	
13.	DTS Premium Sound	DTS 2.0 + Digital Out	
14.	Sound Output (RMS)	10W x 2	
15.	Speaker Type	Down Firing + Full Range	
16.	ConnectShare™	Movie	
17.	OSD Language	English, Spanish, French	
18.	Accessories	Closed Captioning, Game Mode, Eco Sensor, Auto Power Off, Clock & On/Off	

		Timer
19.	HDMI	2
20.	USB	Yes
21.	Component	1
22.	Composite In (AV)	1 (Common Use for Component Y)
23.	RF In (Terrestrial/Cable Input)	1
24.	Digital Audio Out (Optical)	1
25.	Audio Out (Mini Jack)	1
26.	RS232C	Yes
27.	Digital Broadcasting	ATSC / Clear QAM
28.	Power Supply (V)	AC110-240V 60Hz
29.	Remote	Standard Remote Control (TM1240)
30.	Stand	Mini Wall Mount Compatibility
31.	Vesa Wall Mount Compatibility	Yes (200 x 200)
32.	Power Cable	Yes
33.	User Manual	Yes
34.	Warranty	01 years on site comprehensive

### **SPECIFICATION OF PRINTR A4 SIZE**

Sr. #	Functions/Peripherals	Specifications	
1	Printer	Black	
2	Size	A4 and below	
3	Print	Automatic Duplexer both side print (two sides printing)	
4	Resolution	1200x1200 dpi	
5	Print Technology	Laser	
6	Print Resolution Technology	Image	
7	Print Cartridges Number	1	
8	Language	Standard print Language used in Pakistan	
9	Print Management	Default installed SNP, Toolbox FX	
10	Print Speed	Normal up to 52 ppm or above	
11	Connectivity	<ul> <li>1 Hu-Speed USB, 1 Fast Ethernet 10/100 /1000 Wireless (Wifi)</li> <li>Wireless direct3 and NFC touch-to-print4</li> </ul>	
12	Memory	512 MB or above	
13	Processor	800 MHz or above	
14	Duty Cycle	Heavy duty professional	
16	Input	02 Input tray	
17	Output	About 250 sheets output bin, 50- sheets multipurpose tray	
18	Media type	Baond, brochure, coloured, glassy, letter head, photo, plain, recycled, films, transparancy, label, envelopes, etc.	
19	Driver	CD/DVD, software / driver compatible with windows 8, 10 or above and LINIX with user guide, documentation, etc.	
20	Other Accessories	01 cartridges sets in addtion to pre-installed, Power cords round and flat pins both pakistan compatible, network cable, all trays, and other relevant accessories.	
21	Warranty	01 year on site comprehensive	
22	Dealer ship	Authorized Dealership Gold / Higher with manufactural authorization letter	

### Note:

# SPECIFICATION OF PRINTR A4 SIZE (Compliance Sheet)

Sr.#	Functions/Peripherals	Specifications	Compliance/ Bidder Response
1	Printer	Black	
2	Size	A4 and below	
3	Print	Automatic Duplexer both side print (two sides printing)	
4	Resolution	1200x1200 dpi	
5	Print Technology	Laser	
6	Print Resolution Technology	Image	
7	Print Cartridges Number	1	
8	Language	Standard print Language used in Pakistan	
9	Print Management	Default installed SNP, Toolbox FX	
10	Print Speed	Normal up to 52 ppm or above	
11	Connectivity	<ul> <li>1 Hu-Speed USB, 1 Fast Ethernet 10/100 /1000 Wireless (Wifi)</li> <li>Wireless direct3 and NFC touch-to-print4</li> </ul>	
12	Memory	512 MB or above	
13	Processor	800 MHz or above	
14	Duty Cycle	Heavy duty professional	
16	Input	02 Input tray	
17	Output	About 250 sheets output bin, 50- sheets multipurpose tray	
18	Media type	Baond, brochure, coloured, glassy, letter head, photo, plain, recycled, films, transparancy, label, envelopes, etc.	
19	Driver	CD/DVD, software / driver compatible with windows 8, 10 or above and LINIX with user guide, documentation, etc.	
20	Other Accessories	01 cartridges sets in addtion to pre-installed, Power cords round and flat pins both pakistan compatible, network cable, all trays, and other relevant accessories.	

21	Warranty	01 year on site comprehensive	
22	Dealer ship Authorized Dealership Gold /		
		Higher with manufactural	
		authorization letter	

# CONTRACT

#### GOVERNMENT OF PAKSITAN (MINISTRY OF DEFENCE) SURVEY OF PAKISTAN SURVEYOR GENERAL'S OFFICE RAWALPINDI

#### Contract No. /15-G-4/( )/St, dated: - -2021

Refers Supplier's Tender No.

An agreement made the \_\_\_\_\_ day of ------ Two Thousand Twenty One between the President of Pakistan (herein after called the "PURCHASER" on the one part and M/s. ------, "SUPPLIER" on the other part.

Whereby it is agreed that the Purchaser shall purchase and the Supplier shall sell the stores as described in the schedule given hereunder at the price mentioned therein already transmitted through letter of intent subject to the special conditions as follow:

#### SUPPLY SCHEDULE

Description of Stores	Qty/ (Units)	Bill in name of	Rate per unit (Rs.)	Total Cost (Rs.)	Delivery Date
		Drawing & Disbursing Officer, Surveyor General's Office, Survey of Pakistan, Rawalpindi			On or before
			Total:		

**WARNING:** Any information about the sale/purchase of the stores under this contract shall not be communicated to any person, other than the manufacturer of the stores or to any press or agency not authorized by the Surveyor General of Pakistan/Ministry of Defence to receive it. The breach of the undertaking shall be punishable under the Official Secrets Act, 1923

#### **CONTRACT CONDITIONS/CLAUSES:**

- The Surveyor General of Pakistan, Survey of Name of consignee: 1). Pakistan, Faizabad, Rawalpindi. 2). Cost Dubitable to Head: A0900-Physical Assets. A0960-Purchse of Computer Equipment 3). Supplier's Name an Address: 4). Supplier's NTN No. M/s. 5). Supplier's Sales Tax Reg. No: Date of Delivery: 6). Maker's Name & Brand: 7). The stores will be dispatched to the consignee 8). **Dispatch Instructions:** under firm's own arrangements. No part supply will be allowed in any case. Each item will be packed/marked as per relevant paper's particulars governing the supply of store/standard/trade marking worthy of 9). Packing & Marking Instructions: transportation by Rail/Road/Air within Pakistan so as to ensure their safe arrival at ultimate destination without any loss or damaging.
- 10). Inspection:

- a) Inspection Authority:
- Technical Evaluation Committee (TEC) Chairman Technical Evaluation Committee
- b) Inspection Officer:
- Consignee's Premises
- c) Place of Inspection: The Inspecting Officer will be informed 02 working days in advance about the time d) for inspection
- Checking of Stores of Consignee's End: All stores will be checked at consignee's 11). premises in the presence of supplier's representatives. If, for the reasons of economy or other the supplier decides not to nominate his representative for such checking, then advance written notice to this effect will be given by the supplier to the Senior Stores Officer, Surveyor General's Office, Survey of Pakistan, Rawalpindi under intimation to **CPC** prior to or immediately on delivering stores. In such an event, the supplier will clearly under take the decision of consignee with regard to quantities and description of a consignment, which will be taken as final and if any discrepancy found will according be made up by the supplier.

#### 12). Terms of Payment:

- a) 100% payment of value of the stores supplied will be paid to M/s. -----
  - ---, through Cheque by submission of bills duly supported by the **NOC** from **TEC**
- b) Bill will be furnished to the SSO, SGO, Rawalpindi, which will subsequently be submitted to AGPR, Islamabad by the consignee.

#### 13). Taxes & Duties:

- a) Duties & Taxes Applicable: The prices quoted are inclusive of all kinds of duties and taxes. The purchaser shall not be liable for reimbursement of duties and taxes on the contracted goods other than those given in the quoted rates. The payment of element of taxes and duties, which are included in guoted rates, will be made to the supplier only after production of duly authenticated documentary proof of its payment to the respective department. In case fresh taxes and duties are levied by the government after opening of the tender will signing of the contract and during the currency of the contract 9i.e. within the original delivery period) or if the existing rates of taxes are increased after opening of the tender and during the currency of the contract, liability shall be of the purchaser and the same shall be reimbursed by the AGPR, Islamabad to the supplier at actual, on production of documentary proof of his payment duly authenticated. In case of any subsequent decrease in existing or future duty or taxes by the Govt. after opening of tender and during the currency of the contract the liability shall be of the supplier and the supplier shall reimburse the same to AGPR, Islamabad under intimation to purchaser.
- b) For release of payment, the supplier would be required to furnish the following documents to **SSO**, **SGO**.
  - Proof of registration with Sales Tax Department (Copy of Registration i Certificate).
  - Sales Tax Invoice in original showing description/quantity/value of good and ii current amount of Sales Tax leviable thereon.

#### **Bank Guarantee Clause:** 14).

a) To ensure timely and correct supply of stores and smooth execution of warrantee conditions the firm will furnish a bank guarantee/draft from a schedule bank for an amount of 5% of the total value of the contracted stores amounting to Rs. -----to CPC. After completion of warrantee period i.e. 03 years from the date of signing of NOC by PC the supplier will request the CPC through SSO for the withdrawal of bank guarantee/draft. The bank draft will be encased/deposited in SoP's bank account. The bank draft shall be produced by the supplier within 07 days from the date of issue of letter of intent/signing of contract deed and shall remain in force till

completion of the warrantee period beyond the date of inspection.

- b) If the supplier fails to produce the bank guarantee/draft within the specified period, the Surveyor General of Pakistan reserves the right of concealing the contract at the risk and expense of the supplier. In the event of un-satisfactory performance or of any breach of terms of the contract, the bank guarantee/draft shall be forfeited to the government at the discretion of the purchaser. On satisfactory performance of the contract the bank guarantee/draft will be returned to the supplier by CPC, on receipt of clearance from the Consignee.
- Bank guarantee/draft furnished against this contract is un-conditional and encashable at the will of purchaser. Supplier undertakes not to hinder/restrain its encashment through court, extra judicial or any other way (including administrative process).

# 15). Supplier Warranty/Guarantee:

- a) The supplier shall furnish warranty for the stores under supply against defects in material workmanship, and satisfactory performance for one year with parts and one year free service. The stores will be of the high-test grade and consistent with general expectable standard for the stores of type ordered in full conformity with governing specifications and performance of stores with the liability of replacing defective/unacceptable part free of cost within **07 days** by the supplier on receiving the discrepancy report, failing which the purchaser shall have the right to purchase the stores (against the stores declared defective) at the suppliers risk and expense. The supplier also undertakes to make good the deficiency in supply, if any.
- b) Supplier's warranty shall be provided to the consignee along with the store.
- 16). Inspection after Expiry of Delivery Period: Unless informed and directed to the contrary during the currency of the contract, the Inspection Officer will continue the inspection of the stores at firm's risk even after expiry of delivery period. Such acceptance will not prejudice the purchaser's right to cancel the contract or to extend the delivery period with or without liquidated damages.
- 17). Failure and Termination: Should the supplier fail to deliver the stores within stipulated period of supply, on the expiry; the purchaser shall be entitled at his option to take either of the following actions:
  - a) To cancel the contract or purchase from elsewhere the stores not delivered, at risk and expense of the supplier and without notice to him. The supplier shall also be liable to any loss which purchaser sustains on this account but shall not be entitled to any gain of repurchase.
  - b) To make the supplier pay liquidation damages for the period of delays in supply up to the rate of <u>2%</u> of the contract value un-supplied stores per month or part of a month for the period exceeding the original delivery period subject to the provision that total liquidation damages thus levied will not exceed **10%** of the total contract value.
  - c) If contract of the firm is cancelled at 'Risk and Expense' then the latest equivalent of their cancelled stores will be purchased at 'Risk and Expense' of the concerned firm if the cancelled type/category is not available in the market. Similarly an item of contract on FOR (indigenous) basis may be produced at risk and expenses of the firm on FOR (Imported) basis and vice-versa in the interest of the state.
- 18). Force Majeure: Force Majeure shall mean any event, act or other circumstances, not being an event, act or circumstance, under the control of the purchaser or of the supplier. Non-availability of raw material from the manufacturer of stores, or of export permit for the export of the contracted stores from the country of its origin, shall not constitute Force Majeure.

# 19). Special Instructions:

#### Warranty/Guarantee:

- a) The supplier has to provide warranty/guarantee of the stores supplied for a period of 01 year standard warrantee including repair, servicing and replacement of parts from the date of issuance of NOC by the **CPC** The supplier shall replace the defective stores free of cost. Warranty/Guarantee Certificate with regards to all items being supplied would be provided to the consignee along-with the stores.
- b) Trade mark of all items should be quoted clearly. On receipt, if any stores are found to be otherwise it will be changed/ replaced free of cost.
- c) The Supplier will be strictly bound to supply the contracted stores as per tendered specifications, and fulfill all responsibilities in this regard.
- 20). Litigation: In case of any dispute, only court of jurisdiction at Rawalpindi shall have the jurisdiction to decide the matter.

# <u>SIGNATURES</u>

### <u>PURCHASER</u>

#### <u>S U PP L I E R</u>

Designation	Chairman Purchase Committee	
Name		
Signature		
For and on behalf of the President of Islamic Republic of Pakistan.		

Name	
Designation	
Signature	



GOVERNMENT OF PAKISTAN Ministry of Defence SURVEY OF PAKISTAN Surveyor General's Office, Rawalpindi Tele: 051-9290227; Fax: 051-9290229

No. **11**/27-F-2/(2020-21)/St Dated: **19**/January, 2021

To,

The Director Advertisement, Press Information Department, Zero Point, Islamabad.

#### Sub: **PUBLICATION OF CLASSIFIED ADVERTISEMENT**

Please arrange to publish enclosed Tender Notice according to the requirements as specified hereunder:

1	Language	One English (The Dawn) & One Urdu (Daily Jang)
2	Region	Rawalpindi/Islamabad
3	No. of Insertion	Only one insertion
4	Date of Insertion	21-01-2021
5	Special Instructions	Due to limited funds insertion may be restricted as minimum as possible.

2. Necessary funds to meet the expenditure on above advertisement are available. Therefore, after publication of tender, bill in duplicate in the name of Drawing & Disbursing Officer, Surveyor General's Office, Survey of Pakistan, Rawalpindi along with copy of tenders published, may be sent to the undersigned, for payment in due course, please.

### (MUHAMMAD ASGHAR)

Senior Store Officer

#### <u>N.O.O.</u>

Copy to: DDO (SGO) along with a copy of Tender Notice for information, please.



GOVERNMENT OF PAKISTAN Ministry of Defence SURVEY OF PAKISTAN Surveyor General's Office, Rawalpindi Tele: 051-9290227; Fax: 051-9290229 No. /27-F-2/(2020-21)/S

No. /27-F-2/(2020-21)/St Dated: /January, 2021

To,

The System Analyst, PPRA, Federal Bank for Cooperative (FF), G-5/2, Islamabad.

Att: Mr. Rizwan Mahmood

#### Sub: **TENDER NOTICE**

A tender notice regarding purchase of  $13 \times items$  of **Equipment/Furniture** by Survey of Pakistan, Faizabad, Murree Road, Rawalpindi along with bidding documents containing detailed terms and conditions, specifications, evaluation criteria, contract specimen & prescribed tender form is attached herewith.

2. It is requested that above documents may kindly be placed at your website at the earliest. The web page which is audit requirement may also be sent along with your bill.

3. The closing date of the tender is **<u>10-02-2021</u>**, please.

### (MUHAMMAD ASGHAR)

Senior Store Officer

#### <u>N.O.O.</u>

Copy to:	i	Mr. Muhammad Tanvir, DP/MPC	Along with a copy of		
	ii	Mr. Imtiaz Hassan, DT&R/MPC Tender Notice, with the requ			
	iii	Mr. Shah Muhammad, DMP/MPC	ensure your presence on time &		
	iv	Maj. Muhammad Haroon Younus, OC Workshop/MPC	date of opening mentioned therein, please.		
	v	DDO (SGO) along with a copy of Tender Not	ice for information, please.		
	vi	Incharge CDBA (MPO) with the request to upload the enclosed Tender Notice on the			
		department's website, please.			